



BINA PAINT

Colours Of Happiness



GLOMEL

GLOSS FINISH ENAMEL PAINT



GREENproduct



Certification No.:
MBC0055



**SIRIM
ECO-LABEL**
Certification No.:
ELB0323001



GLOMEL

GLOSS FINISH ENAMEL PAINT

GLOMEL GLOSS FINISH is a premium grade alkyd enamel paint, specially formulated for exterior and interior metal and wood surfaces with excellent gloss appearance, excellent durability even under tough weather conditions and outstanding resistance to fungus and chalking.



OFF WHITE GM2300



FIESTA YELLOW GM2460



GRACEFUL GM2010



JADE GREEN GM2055



ASH GREY GM2306



IVORY GM2130



SUNFLOWER GM2505




PEARL BLUE GM2477



HAZE GREEN GM2117



VENUS GM2406



MAPLE GM2366



GOLD CANARY GM2678



VARSITY BLUE GM2281



GRASSY GM2560



EXEC GREY GM2335



HONEY CREAM GM2405



GOLD SAHARA GM2328



PARADISE BLUE GM2365



OLIVE GM2653



PAPIER GREY GM2139



CITRUS GREEN GM2303



SOAKSTONE GM2301




MARINE BLUE GM2649



CONIFER GM2509



GRAPHITE GM2806



TURQOISE GM2401



WIRA BLUE GM2471



SPRUCE GM2510



NIGHTFALL GM2182



CREAM GM2363



BARBARY GOLD GM2329



PEACH PINK GM2324



SOFT VIOLET GM 2115



GOLDEN SAND GM2319



OAK GM2322



MANDARIN GM2331



CHARMED VIOLET GM2555



SWEET DREAM GM2502



RUSSET BROWN GM2332



SIGNAL RED GM2402



GRAPIES GM2056



CAMEL GM2070



MAHOGANY GM2136



FLAMINGO GM2432



PLUM RED GM2154



SIRIM
ECO-LABEL
Certification No :
ELB0323001



CARNIVAL RED GM2507

Also Available

WHITE GM2000

BLACK GM2001

The colours on this card are as close to actual paint colours as modern printing techniques will allow.



TRUNKING GM2003



TNB GREY GM2004



TNB RED GM2005



TNB BLUE 2006

GLOMEL

GLOSS FINISH ENAMEL PAINT

GLOMEL GLOSS FINISH

GLOMEL GLOSS FINISH is a premium grade alkyd enamel paint, specially formulated for exterior and interior metal and wood surfaces with excellent gloss appearance, excellent durability even under tough weather conditions and outstanding resistance to fungus and chalking.

SURFACE PREPARATION

Wood and Metal Surface.

Ensure surfaces to be painted completely dry & free from dirt, grease and other contamination. For surfaces that have been painted, scrape the remaining paint. Problem areas should be smoothed with sandpaper. For metal surfaces, remove rusty areas by scrubbing or scouring wire. Then, partially smoothed the surface with sandpaper, clean the surface and let dry.

APPLICATION DATA

Touch Dry : Depending on the temperature and humidity (4 hours).

Hard Dry : 8 - 10 hours.

Coverage : 13 - 15m² / litre (depending on the surface).

Recoating Time : 10 hours.

No. of Layer : Minimum 2 layers.

Use on Wood :

- i. 1 layer of Bina Aluminium Wood Primer
- ii. 1 layer of Bina Undercoat
- iii. 1 - 2 layers Bina Glomel

Use on Metal :

- i. 1 layer of Bina Red Oxide Zink Phosphate /Chromate
- ii. 1 layer of Bina Undercoat
- iii. 1 - 2 layers of Bina Glomel

DIRECTION FOR USE

Stir the paint thoroughly. Use tools such as brush, roller or spray gun to paint.

To finish as well, do not use thinners. If necessary, thin with general purpose Thinner /Mineral Turpentine. Clean all equipment with thinner immediately after use.

GLOMEL GLOSS FINISH

GLOMEL GLOSS FINISH ialah cat enamel gred premium, dirumus khas untuk bahagian luar dan dalam bagi permukaan logam dan kayu dengan permukaan kilat yang bermutu, serta ketahanan yang sangat baik walaupun dalam perubahan cuaca yang ketara dan juga mencegah daripada kulat dan masalah berkapur.

PENYEDIAAN PERMUKAAN

Permukaan Kayu dan Besi.

Pastikan permukaan yang hendak dicat itu kering & benar-benar bebas daripada kotoran, gris dan pencemaran lain. Untuk permukaan yang telah dicat, kikiskan lapisan cat yang tertinggal. Kawasan bermasalah hendaklah dilicinkan dengan kertas pasir. Untuk permukaan besi, singkirkan bahagian berkarat. Kemudian, licinkan permukaan dengan kertas pasir, bersihkan permukaan dan biarkannya kering.

DATA PENGGUNAAN

Kering sentuh : Bergantung pada suhu dan kelembapan (4 jam).

Kering sempurna : 8 - 10 jam.

Liputan : 13 - 15m² / liter (bergantung pada keadaan permukaan).

Ulang cat : 10 jam.

Bil. Lapisan : Minimum 2 lapisan.

Kegunaan pada Kayu :

- i. 1 lapisan Bina Aluminium Wood Primer.
- ii. 1 lapisan Bina Undercoat.
- iii. 1 - 2 lapisan Bina Glomel.

Kegunaan pada Besi :

- i. 1 lapisan Bina Red Oxide Zink Phosphate /Chromate
- ii. 1 lapisan Bina Undercoat
- iii. 1 - 2 lapisan Bina Glomel

PERATURAN

Kacau cat hingga sebati. Gunakan alatan seperti berus, penggelek atau penyembur untuk mengecat. Untuk kemasan yang memuaskan, jangan gunakan pencair. Jika perlu, cairkan dengan sedikit Thinner/Mineral Turpentine. Bersihkan semua peralatan dengan Thinner serta-merta selepas menggunakannya.

BINA

The Perfect Solution

BINA INTEGRATED INDUSTRIES SDN. BHD. (715329-T)

HEAD OFFICE

No. 9-3, Tingkat 2 Jalan SP 2/9,
Taman Serdang Perdana, 43300 Seri Kembangan, Selangor.
Tel: +603. 8942 3446 / 4593 . Fax: 03 8948 5687

FACTORY

No. 16 Jalan 9/3, Taman IKS, Seksyen 9,
43650 Bandar Baru Bangi, Selangor.
Tel: +603 8926 6167 / 8922 2162 . Fax: 03 8926 6168

website: www.binatech.biz



EXTERIOR



INTERIOR



10 Hours
Recoat



THINNER



Made In
MALAYSIA

