



PRODUCT DATA DECORATIVE COATING Duracourt

DURACOURT

SPORT COURT COATING

DESCRIPTION

DURACOURT is a single component water-based acrylic coating. The dry coating is flexible, non-slippery, tough, good wear resistance, excellent resistant to fungus growth and weathering. It is specially designed for surfacing of tennis court, badminton court and others. Apply as a non-slip and decorative coating on asphaltic cement, concrete or masonry surface outdoor or indoor.

ADVANTAGES

- Non-reflective and non-skid.
- No fire hazard – can be used in areas where solvent-based coatings are not allowed.
- Excellent adhesion to concrete, bitumen and steel surfaces.
- Good resistance against UV and ponding water (48 hrs).
- Easy to clean – application tools and equipment can be cleaned easily with water after use.

- Fast dry – touch dry in 1 hour and can be top-coated in 4 hours.
- Chemical resistance - Dry coat resistant to water, grease, oil, kerosene, salt and detergent.

METHOD OF APPLICATION

- The surface to be coated must be thoroughly cleaned and degreased to ensure that oil, grease and other surface contaminants are removed. New concrete shall be allowed to cure for at least 28 days before application.
- DURACOURT can be applied by rollers, brushes or rubber squeegee.
- Mix materials with a mechanical stirrer or a stick to ensure good leveling and colour consistency during application. Can be further mix with aggregates and clean water for squeegee application.
- It may be thinned with 1 part of clean water to 4 parts of DURACOURT by volume for application onto hot surface heated by direct sunlight.
- Two coats are recommended. Subsequent coat shall be applied on a thoroughly dry coat. Recommended coverage : 0.2 – 0.4 litre per m²

Cleaning : Clean all equipment and tools with water immediately after use. Dry material can be removed with strong solvent.

PRODUCT DATA
DECORATIVE COATING
Duracourt

TECHNICAL SPECIFICATIONS

No. of Components	: One
Finish	: Matt
Weight Solids	: 65 ± 2 %
Theoretical Coverage	: 3.0 m ² /kg @ 2.5 microns DFT
No. of coats recommended	: Two
Drying Time (Ventilated Area)	: Touch dry – 1 hour Topcoat – 4 hours
Packing Size	: 20 kg pail or 200 kg drum
Colours	: Green, Red, Blue and White
Shelf-life	: 12 months under cover and in a cool, dry place in unopened container.
Thinning & Cleaning	: Clean water



®

BINA INTEGRATED INDUSTRIES SDN. BHD. (715329-T)

No. 16, Jalan 9/3, Taman IKS, Seksyen 9, 43650 Bandar Baru Bangi, Selangor

tel: +603-8926 6167

fax: +603-8926 6168

www.binatech.biz

email : factory@binatech.biz



WATERPROOFING • PROTECTIVE COATING • INDUSTRIAL FLOORING
STRUCTURAL REPAIR • SPORTS & RECREATIONS

CERTIFIED TO ISO 9001 : 2000
CERT NO. : AR 4425