



BINA PRIMACOURT

MULTIPURPOSE DECORATIVE FLOOR COATING

DESCRIPTION

BINA PRIMACOURT is single component water base acrylic coating use for multipurpose decorative floor coating. The dry coating is flexible, excellent resistance to fungus growth and weathering. It is specially design for protection of the internal and external masonry substrate concrete floor and sport coating.

Recommended for non-immersion services and impart non-kid property on slippery surfaces.

It is easy to apply, washable, fungus resistance and environmental friendly.

ADVANTAGES

- Non -reflective and non-skid
- No fire hazard-can be used in areas where solvent based coatings are not allowed
- Excellent adhesion to masonry, brick, plastering substrate and fibre board.
- Good resistance against UV
- Easy to clean-application tools and equipment can be cleaned easily with water after use

METHOD OF APPLICATION

Surface Preparation:

• The surface should be clean (free from oil, grease and other surface contaminants), compact and dry. The surface should be carefully inspected to determine the preparation work to be earned out. Remove all the loose paints by using gross brush or high-pressure waterjet and ensure that surfaces are free from contaminations and oil stains prior to painting work in order to have higher and maximum performance. Do not apply paint on wet walls or when raining.

• For new cement surfaces, ensure that the surfaces are thoroughly dry before painting. The concrete shall be allowed to cure for at least 14 days before application of coatings is allowed (28 days recommended). Other-wise, premature paint failure may occur.

- Bina Primacourt can be applied by rollers or brushes

RECOMMENDED COATING SYSTEM:

One coat of: Sealer/ Primer: Bina Sealer Exterior Premium
2-3 coats of Top coat Bina Primacourt

STORAGE: The product must be kept in a cool and dry as well as ventilated place.

CLEANING: Clean all application tools with clean water immediately after use.

HEALTH AND SAFETY

See Health and Safety section in Data Manual. Note should also be taken of all relevant legislation ruling in individual countries. Consult manufacturer's material safety data sheet (MSDS)

TECHNICAL SPECIFICATIONS

Physical Data

Generic	Pure Acrylic
Component	Single
Curing Mechanism	Water based
Finish	Low Sheen
Application	Brush or roller
Color	Refer to standard colour
Recommended Sealer/Primer	BINA Sealer Exterior Premium (Theoretical coverage horizontal 6m ² /L per layer)
Volume Solids	50±3%
Recommended Thickness	100 to 120 microns DFT
Theoretical Coverage	Approximate 8 m ² /litre @ 50 microns (depends on substrate condition)
No. of coats recommended	two coats
Drying Time	At 25°C, Touch dry - 30 minutes Recoatable - minimum 2 hours (varies with temperature and humidity)
Thinner/cleaner	Water
Shelf life	Up to 2 year from manufacturing date in tight sealed container when stored indoor at room temperature

SAFETY PRECAUTIONS

Before use: Read instructions for use and precautionary labels on container.

During use: Avoid contact with skin. Ensure good ventilation during use and avoid inhalation of spray mist and fumes. Wear suitable respiratory or face mask. Wear suitable eye protection and avoid ingestion of paints.

Storage: Store away from heat and sources of ignition. Avoid Prolong exposure to direct sunlight.

Disposal: Follow local and national regulations.

Spillage: Remove all sources of ignition. Avoid prolong exposure to vapours. Clean up with absorbent materials. Ventilated area. Do not wash into drains.

EMERGENCY TREATMENT

Eyes: Flush immediately with water. Seek medical helps.

Skin: Remove contaminated clothing. Use appropriate skin cleaner. Wash well with soap and water.

Inhalation: Move into fresh air. Loosen collar and avoid excessive exertion.

Ingestion: Seek immediate medical advice. DO NOT induce Vomiting



R

BINA INTEGRATED INDUSTRIES SDN. BHD. (715329-T)

No. 10, Jalan 9/7, Taman IKS, Seksyen 9, 43650 Bandar Baru Bangi, Selangor

tel: +603-8926 0012

fax: +603-8926 0023

www.binapaint.com.my

email : info@binapaint.com.my

WATERPROOFING • PROTECTIVE COATING • INDUSTRIAL FLOORING
STRUCTURAL REPAIR • SPORTS & RECREATIONS



CERTIFIED TO ISO 9001 : 2000
CERT NO : AR 4425