



PRODUCT DATA
DECORATIVE COATING
BINA MAXICOAT LITE

BINA MAXICOAT LITE

INTERIOR WALL & CEILING MATT
FINISH

DESCRIPTION

BINA MAXICOAT LITE is specially formulated water-based copolymer emulsion coatings. It has Vinyl Acetate Resin content which provide a matt finishing to almost kind of surface. It has smooth with low smell and nontoxic which is an environmentally friendly coating.

TYPICAL USES

BINA MAXICOAT LITE is widely recommended for area such as:

- i. Interior walls
- ii. Concrete and masonry such as wall, ceiling, asbestos, hard and soft boards.

ADVANTAGE

- Easy to apply
- Good storage stability
- Fragrance added
- Satin matt colour

METHOD OF APPLICATION

SURFACE PREPARATION

- The surface should be clean (free from oil, grease and other surface contaminants), the surface should be carefully inspected to determine the preparation work to be earned out. Remove all loose paints by using gross brush or high-pressure waterjet and ensure that surfaces are free from contaminations and oil stains prior to painting work in order to have higher and maximum performance. Do not apply paint on wet wall or when raining.

- For new cement surfaces, ensure that the surfaces are thoroughly dry before painting. The concrete shall be allowed to cure for at least 14 days before application of coatings is allowed (28 days recommended). Otherwise, premature paint failure may occur.

STORAGE: The product must be kept in a cool and dry as well as ventilated place

CLEANING: Clean all application tools with clean water immediately after use.

HEALTH AND SAFETY: See Health and Safety section in Data Manual. Note should also be taken of all relevant legislation ruling in individual countries. Consult manufacturer's material safety data sheet (MSDS).

TECHNICAL SPECIFICATIONS

Generic Component	Vinyl Acetate Single
Curing Mechanism	Water based
Finish	Matt
Application	Airless or conventional spray, brush or roller
Colour	Wide range
Solid Content	55±3%
No of coats recommended	Minimum 2 coats
Theoretical Coverage	10-12 m ² /litre @ 30 microns (depends on substrate condition)
Drying Time, 25-30°	Touch dry: 15 minutes Recoating: 2 hours (Varies with temperature and humidity)
Thinner/cleaner	Water
Shelf life	1 year after manufacturing date when stored indoor at 5 to 38°C



PRODUCT DATA
DECORATIVE COATING
BINA MAXICOAT LITE

SAFETY PRECAUTIONS

Before use: Read instructions for use and precautionary labels on container.

During use: Avoid contact with skin. Ensure good ventilation during use and avoid inhalation of spray mist and fumes. Wear suitable respiratory or face mask. Wear suitable eye protection and avoid ingestion of paints

Storage: Store away from heat and sources of ignition. Avoid Prolong exposure to direct sunlight.

Disposal: Follow local and national regulations
Rev Number:

Spillage: Remove all sources of ignition. Avoid prolong exposure to vapours. Clean up with absorbent materials. Ventilated area. Do not wash into drains.

EMERGENCY TREATMET

Eyes: Flush immediately with water. Seek medical helps.

Skin: Remove contaminated clothing. Use appropriate skin cleaner. Wash well with soap and water.

Fire: Fight fire with foam or dry powder

Inhalation: Move into fresh air. Loosen collar and avoid excessive exertion.

Ingestion: Seek immediate medical advice. DO NOT induce Vomiting

REVISION: 01 (2019)



BINA INTEGRATED INDUSTRIES SDN BHD (715329-T)
No. 10 Jalan 9/7, Taman IKS, Seksyen 9, 43650 Bandar Baru Bangi, Selangor
Tel: +603- 8926 0012/0013 Fax:+603-8929 0023
Website: www.binapaint.com.my Email: info@binatech.biz

WATERPROOFING • PROTECTIVE COATING • INDUSTRIAL FLOORING
STRUCTURAL REPAIR • SPORTS & RECREATIONS



ISO 9001:2015 MS 1900:2014
RCI QMS 01768 RCI-QMS 0013.7